

# LEADERS IN LIFTING SAFETY World's Largest CROSBY Distributor 5833 ARMOUR DR. HOUSTON,TX 77020 PH#713-674-5631 FX#713-674-8352



# **CERTIFICATE OF TEST**

TEST DATE: 4/21/2017

CUSTOMER: J.J. OILFIELD SERVICES

HHI ORDER: 1047532

NUMBER OF PIECES TESTED: 1 SET

TEST ID #: H1047532-1-1PM

DESCRIPTION: 2-3/4 IN X 120 IN 350 TON SET OF EXTENDED BAILS W/PINS

**WORKING LOAD LIMIT: 350 TONS** 

TEST LOAD: 262.5 TONS 5 MIN HOLD EACH LINK

QUALITY ASSURANCE SIGNATURE:

ModnysElkins

# RODNEY ELKINS

This certifies the described products meet the above specifications. Load measuring instrument is accurate  $\pm 1\%$  of reading as specified by ASTM E-4. Upon conclusion of testing no obvious defects were noted.

CAUTION: It is recommended that a nondestructive test be performed following the load test in order to reveal any defects caused as a result of the load applied.

#### DISCLAIMER



# World's Largest CROSBY Distributor 5833 ARMOUR DR. HOUSTON,TX 77020 PH#713-674-5631 FX#713-674-8352



# **CERTIFICATE OF TEST**

TEST DATE: 4/21/2017

CUSTOMER: J.J. OILFIELD SERVICES

HHI ORDER: 1047532

NUMBER OF PIECES TESTED: 1 SET

TEST ID #: H1047532-1-2PM

DESCRIPTION: 2-3/4 IN X 120 IN 350 TON SET OF EXTENDED BAILS W/PINS

**WORKING LOAD LIMIT: 350 TONS** 

TEST LOAD: 262.5 TONS 5 MIN HOLD EACH LINK

QUALITY ASSURANCE SIGNATURE:

RodnyElkins.

#### RODNEY ELKINS

This certifies the described products meet the above specifications. Load measuring instrument is accurate  $\pm 1\%$  of reading as specified by ASTM E-4. Upon conclusion of testing no obvious defects were noted.

CAUTION: It is recommended that a nondestructive test be performed following the load test in order to reveal any defects caused as a result of the load applied.

### DISCLAIMER

# I HOLLOWAY

LEADERS IN LIFTING SAFETY World's Largest CROSBY Distributor 5833 ARMOUR DR. HOUSTON,TX 77020 PH#713-674-5631 FX#713-674-8352



# POST-MT EXAMINATION REPORT

DATE: 4/21/2017

CUSTOMER: JJ OILFIELD SERVICES

HHI ORDER: 1047532

**OUANTITY: 1 SET** 

TEST ID #: H1047532-1-1PM

DESCRIPTION:2-3/4 IN X 120 IN 350 TON SET OF EXTENDED BAILS W/PINS

SCOPE OF INSPECTION: EYES AND 18 INCHES AWAY

NDE SPECIFICATION: SOP 2.8-3 REV F

NDE METHOD: Wet Visible

MAGNETIZING SOURCE:

YOKE (X) YOKE SERIAL#: (17465) YOKE LIFTING FORCE VERIFIED (X)

MAG UNIT - [] P-500 [] M-2040 [] M-2060

No. TURNS:[] AMPERES:[]

LIGHT INTENSITY EQUIPMENT SERIAL #: ( ) LIGHT INTENSITY VERIFIED ( )

[X] CONTINUOUS MAGNETIZATION [] RESIDUAL MAGNETIZATION

BATH/INDICATOR USED: 7HF

BATCH #:16G10K

BRAND: MAGNAFLUX

SURFACE TEMPERATURE: 80 F

RELEVANT INDICATIONS: NO INDICATIONS FOUND AT THE TIME OF INSPECTION.

ACCEPT [X]

REJECT []

COMMENTS:

INSPECTED BY:

JERONIMO PLATA #875 (LEVEL II SNT-TC-1A in MT)

WITNESS SIGNATURE:

DISCLAIMER



LEADERS IN LIFTING SAFETY World's Largest CROSBY Distributor 5833 ARMOUR DR. HOUSTON,TX 77020 PH#713-674-5631 FX#713-674-8352



# POST-MT EXAMINATION REPORT

DATE: 4/21/2017

CUSTOMER: JJ OILFIELD SERVICES

HHI ORDER: 1047532

QUANTITY: 1 SET

TEST ID #: H1047532-1-2PM

DESCRIPTION:2-3/4 IN X 120 IN 350 TON SET OF EXTENDED BAILS W/PINS

SCOPE OF INSPECTION: EYES AND 18 INCHES AWAY

NDE SPECIFICATION: SOP 2.8-3 REV F

NDE METHOD: Wet Visible

MAGNETIZING SOURCE:

YOKE (X) YOKE SERIAL#: (17465) YOKE LIFTING FORCE VERIFIED (X)

MAG UNIT - [] P-500 [] M-2040 [] M-2060

No. TURNS:[] AMPERES:[]

LIGHT INTENSITY EQUIPMENT SERIAL #: ( ) LIGHT INTENSITY VERIFIED ( )

[X] CONTINUOUS MAGNETIZATION [] RESIDUAL MAGNETIZATION

BATH/INDICATOR USED: 7HF

BATCH #:16G10K

BRAND: MAGNAFLUX

SURFACE TEMPERATURE: 80 F

RELEVANT INDICATIONS: NO INDICATIONS FOUND AT THE TIME OF INSPECTION.

ACCEPT [X]

REJECT []

COMMENTS:

INSPECTED BY:

JERONIMO PLATA #875 (LEVEL II SNT-TC-1A in MT)

WITNESS SIGNATURE:

DISCLAIMER